

FESCO DRAIN, FESCO DRAIN S

E-p14


1st edition February 2015

Description

Tapered insulation boards consisting of expanded perlite, binders and fibres.

FescoDrain S insulation boards have a coating of bitumen (approx 350 g/m²) protected by a sacrificial polypropylene film, for use with torch-applied roofing felts.

FescoDrain insulation meets the requirements of EN 13169. Production is covered by ISO 9001 and ISO 14001 certifications.



Uses

Thermal insulation under waterproofing systems on concrete, metal, timber, or lightweight concrete roof decks.

FescoDrain is suitable for all types of public or private building with self-protected or ballasted waterproofing systems; insulated parking decks for light or heavy vehicles, rooftop gardens with ballasted, mechanically fastened or fully bonded or torch-applied waterproofing.

Suitable for new work and refurbishment, also as a top layer to organic insulation boards.

▶ See the relevant "Application" brochure.

Agrément Certificates available
Insurance rating: meets CC2-APSAD, DIN 18234
CE marking (Fesco)

Advantages

- Compression and indentation resistant
- Resists heavy foot traffic both during and after installation
- Excellent dimensional stability
- Ecological and recyclable
- Certified thermal properties
- Compatible with hot bitumen
- Compatible with Fesco SP, for the application under asphalt for light vehicles car parks
- Compatible with solar photovoltaic panels
- Optimizes the drainage

Standard dimensions

Length	1200 mm		
Width	600 mm		
Slopes	1%	1.67%	2%
	2.5%	3.33%	4.17%

Other dimensions and slopes upon request.

Characteristics

See Fesco or Fesco S product data sheet.